

STS AUTO LEVEL

STS AUTO-LEVEL

- **Sealed-type body :**
no damage from fluctuation of the weather.
- **Multi-type bottom plate :**
convertible to both flat & dome head tripod.
- **Automatic compensating function (Magnet)**
- **Having 30cm of minimum focusing range,**
efficient for the working at narrow space.
- **With hard case which surely protects your auto-level.**



24X

A button for automatic compensating function.



26X

A button for automatic compensating function.



Item	20XG	24XG	26XG	28XG	32XG
Item No.	2-009G	2-010G	2-020G	2-030G	2-050G
Standard deviation (1km)	±2.5mm	±2.0mm	±1.5mm	±1.5mm	±1.0mm
Objective lens	30mm	34mm	40mm	40mm	40mm
Magnification	20X	24X	26X	28X	32X
Minimum focusing range	30cm	30cm	30cm	30cm	30cm
Automatic compensating range	±15'	±15'	±15'	±15'	±15'
Sensitivity of round shaped bubble unit	10'/2mm	10'/2mm	10'/2mm	10'/2mm	10'/2mm
Weight (net)	1.3kg	1.3kg	1.3kg	1.3kg	1.3kg
Waterproof	IP55 type	IP55 type	IP55 type	IP55 type	IP55 type



ISO 9001 Certified



ISO 9001 Certificate no.900982



JSIMA
Japan Surveying Instruments Manufacturers' Association

JSIMA is an organization aiming at development and advancement of Japanese Land Surveying Industry. We, STS, are the formal member of this organization.

DUE TO PRODUCT IMPROVEMENT, THE SPECIFICATION & THE APPEARANCE MAY CHANGE WITHOUT ANY NOTICE.

STS Corporation

1-1603 Kounosu, Tenpaku-Ku, Nagoya 468-0003 JAPAN
Tel: 81-52-847-8880 Fax: 81-52-847-8883

<http://www.sts-s.co.jp> E-mail : sts-s@sts-s.co.jp